



249.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Rockchip® ARM Cortex A17 RK3288 Quad-core 1.8GHz
- Onboard 1333 /2GB DDR3L DRAM Max. 4GB
- Onboard 8G Flash ROM Max 32GB
- Support 1\* Realtek® RTL8211E-VB Gigabit LAN, 1\* Realtek® RTL8723BS 802.11 b/g/n
- Support 1\* Micro SD Socket (Max 64G)
- 1\* USB2.0, 1\* OTG, 1\* RS485, 1\* HDMI, 1\* Total switch control
- 12V DC-in

|                 |                                                                                                                                                                                                   |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MB Model        | – JARMB3288W-2N (3.5" SBC)                                                                                                                                                                        |
| Part No         | – HBJC921R3288-2N                                                                                                                                                                                 |
| CPU/Chipset     | – Rockchip® ARM Cortex A17 RK3288 1.8GHz Quad core<br>– Rockchip® RK808-B                                                                                                                         |
| Memory          | – 2GB/1333MHz DDR3L (Max 4GB)                                                                                                                                                                     |
| Storage         | – 8GB Flash (Max 32GB)                                                                                                                                                                            |
| Network         | – 1 * REALTEK RTL8211E-VB Gigabit LAN<br>– On board 802.11 a/b/g/n/ac, 2.4G<br>– On board BT-V4.0 BLE                                                                                             |
| Rear Panel I/O  | – 1 * RJ45<br>– 1 * HDMI<br>– 1 * Audio Jack<br>– 1 * USB2.0<br>– 1 * OTG (Option USB2.0)<br>– 1 * RS485<br>– 1 * Micro SD Socket<br>– 1 * Power button<br>– 1 * SIM Card Socket<br>– 12V DC-Jack |
| Front Panel I/O | – 2 * Antenna hole<br>– 1 * Total switch control                                                                                                                                                  |
| Power Source    | – DC 12V-5.0A<br>– AC 90~240V input                                                                                                                                                               |
| Compliance      | – RoHS, CE, FCC, CE-LVD                                                                                                                                                                           |
| Temperature     | – Operating Temperature: -10 ~ 60° C<br>– Storage Temperature: -20 ~ 65° C                                                                                                                        |
| Dimensions      | – 190 (W) x 115 (D) x 22 (H) mm                                                                                                                                                                   |
| OS Support      | – Android 5.1, Linux Debian 9.0                                                                                                                                                                   |

---

|            |                           |
|------------|---------------------------|
| Warranty   | – 1 Year limited warranty |
| Life Cycle | – Till 2023 Q1            |